


GUELL 1



Scan the QR-code for the latest information


■ GR-94 / Metallic grey / Textured

LED floodlight for indoor and exterior lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, tempered, flat toughened glass diffuser
- High-performance polished, oxidised, iridescence-free pure aluminium reflector (Al 99.99)
- Anti-ageing silicone sealing gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- Openable and maintainable luminaire (future-proof)
- Dimmable ballast available. Consult factory
- Other colour temperatures (CCT) and different colour rendering index (CRI) options available. Consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Design by GIORGIO LODI



Grotte di Frasassi - Genga - Italy



GUELL 1 S/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
51	I	-	80	4000	S/W	-	8099	6860	■	3115049	
51	I	-	80	3000	S/W	-	7660	6607	■	3115050	-
36	I	-	80	4000	S/W	-	6074	5391	■	3115054	
36	I	-	80	3000	S/W	-	5748	5223	■	3115055	-

DALI and 5000K versions are available on web



GUELL 1 A/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
51	I	-	80	4000	A40/W	-	8099	6505	■	3115059	
51	I	-	80	3000	A40/W	-	7660	6249	■	3115060	
36	I	-	80	4000	A40/W	-	6074	5112	■	3115064	
36	I	-	80	3000	A40/W	-	5748	5028	■	3115065	

DALI and 5000K versions are available on web



GUELL 1 C/I

IP66 - IK07 - 650 °C


LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
52	I	-	80	4000	C/I	-	7276	6657	■	3115047	-
52	I	-	80	3000	C/I	-	7059	6401	■	3115046	-
39	I	-	80	4000	C/I	-	5558	5335	■	3115044	-
39	I	-	80	3000	C/I	-	5392	5130	■	3115041	-

DALI and 5000K versions are available on web



OPTIONAL ACCESSORIES


DESCRIPTION	COLOR	PART NUMBER	PRONTO
GUELL 1			
Protective grid GUELL 1		14172902	-
Connection box IP 66		14174220	-
Wall support 500 mm/19.69" GUELL 1/2	■	14173394	
Wall support 1000 mm/39.37" GUELL 1/2	■	14173494	
Single pole top support GUELL 1	■	14453194	
Double pole top support GUELL 1	■	14453294	
GUELL 1 A/W - GUELL 1 S/W			
Soft glass GUELL 1	■	14173294	-
GUELL 1 A/W			
Louvre GUELL 1 Asymmetrical		14173120	-
GUELL 1 S/W			
Louvre GUELL 1 Symmetrical		14173020	-
GUELL 1 C/I			
GUELL 1 C/I frosted glass	■	14476594	-



14172902



14174220



14173394




14173494




14453194




14453294




14173294



14173120



14173020



14476594