



MIMIK 30 CP/T3




Part number	303848
Lampholder:	LED
Light Source:	LED
Wattage:	30 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	70
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	PEDESTRIAN AND CYCLE REFLECTOR Type 3
Lightsource lumen output:	4160 lm
Luminaire lumen output:	2558 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°
ULR:	0%



Description

- Indoor and outdoor wall-mount fixture, including:
- Polyester powder coated die-cast aluminium housing
 - Flat, transparent, tempered glass diffuser, screen printed on the inner surface for MIMIK series
 - Silicone gasket
 - LED versions include 220/240 V 50/60 Hz safety transformer
 - "MIMIK fixtures are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
 - Powder polyester painting process optimized against UV rays in 13 different steps
 - "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

