

NIKKO+21/27

design by ROBERTO FIORATO




Series of wall, ceiling and post mounted luminaires in two dimensions for indoor and outdoor lighting, comprising:


- Housing, trim, wire guards and vertical VISA in painted die-cast aluminium
- Pressed glass diffuser, white painted inside, secured with the ring
- Reflector and components bracket made of aluminium
- Foam silicone gasket
- Stainless steel locking screws
- The PC versions are equipped with vandal-resistant opal technopolymer diffuser, 960°C glow wire test rated




- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured



NIKKO+
21



NIKKO+
21/G




NIKKO+
21/VV




Please visit our web site
www.performanceinlighting.com
for the latest updated versions available.


GENERAL OUTDOOR



NIKKO+
27



NIKKO+
27/G




NIKKO+
27/VV

NIKKO+21 LED

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER	
Power LED 220-240 V 50/60 Hz															
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	479 lm	80	10	50000 h	●	301410
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	481 lm	80	10	50000 h	●	3014106
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	479 lm	80	10	50000 h	●	301411
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	481 lm	80	10	50000 h	●	3014116
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	479 lm	80	10	50000 h	○	301409
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	481 lm	80	10	50000 h	○	3014096



NIKKO+21

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	●	002001
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	●	002002
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	○	002000



NIKKO+21/G LED

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER	
Power LED 220-240 V 50/60 Hz															
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	255 lm	80	10	50000 h	●	301656
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	255 lm	80	10	50000 h	●	3016566
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	255 lm	80	10	50000 h	●	301657
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	255 lm	80	10	50000 h	●	3016576
LED	10 W	I	-	80	4000	-	S/EW	-	738 lm	255 lm	80	10	50000 h	○	301655
LED	10 W	I	-	80	3000	-	S/EW	-	672 lm	255 lm	80	10	50000 h	○	3016556



NIKKO+21/G

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	●	002011
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	●	002012
E27	1x60 W	I	✓	-	-	-	S/EW	-	-	-	-	-	○	002010



NIKKO+21/VV LED

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER	
Power LED 220-240 V 50/60 Hz															
LED	10 W	I	-	80	4000	-	A/EW	-	738 lm	233 lm	80	10	50000 h	●	301660
LED	10 W	I	-	80	3000	-	A/EW	-	672 lm	236 lm	80	10	50000 h	●	3016606
LED	10 W	I	-	80	4000	-	A/EW	-	738 lm	233 lm	80	10	50000 h	●	301661
LED	10 W	I	-	80	3000	-	A/EW	-	672 lm	236 lm	80	10	50000 h	●	3016616
LED	10 W	I	-	80	4000	-	A/EW	-	738 lm	233 lm	80	10	50000 h	○	301659
LED	10 W	I	-	80	3000	-	A/EW	-	672 lm	236 lm	80	10	50000 h	○	3016596



NIKKO+21/VV

IK05 0.70J xx3


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS θ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
E27	1x40 W	I	✓	-	-	-	A/EW	-	-	-	-	-	●	002021
E27	1x40 W	I	✓	-	-	-	A/EW	-	-	-	-	-	●	002022
E27	1x40 W	I	✓	-	-	-	A/EW	-	-	-	-	-	○	002020



NIKKO+27 LED

IK06 1J xx3


LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	592 lm	80	10	50000 h	●	301414
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	546 lm	80	10	50000 h	●	3014146
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	592 lm	80	10	50000 h	●	301415
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	546 lm	80	10	50000 h	●	3014156
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	592 lm	80	10	50000 h	○	301413
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	546 lm	80	10	50000 h	○	3014136



NIKKO+27

IK06 1J xx3


LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	●	002031
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	●	002032
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	○	002030



NIKKO+27/G LED

IK06 1J xx3


LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	270 lm	80	10	50000 h	●	301664
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	317 lm	80	10	50000 h	●	3016646
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	270 lm	80	10	50000 h	●	301665
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	317 lm	80	10	50000 h	●	3016656
LED	13,5 W	I	-	80	4000	-	S/EW	-	1002 lm	270 lm	80	10	50000 h	○	301663
LED	13,5 W	I	-	80	3000	-	S/EW	-	912 lm	317 lm	80	10	50000 h	○	3016636



NIKKO+27/G

IK06 1J xx3


LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	●	002046
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	●	002047
E27	1x100 W	I	✓	-	-	-	S/EW	-	-	-	-	-	-	○	002045



NIKKO+27/VV LED

IK06 1J xx3


LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	13,5 W	I	-	80	4000	-	A/EW	-	1002 lm	269 lm	80	10	50000 h	●	301668
LED	13,5 W	I	-	80	3000	-	A/EW	-	912 lm	327 lm	80	10	50000 h	●	3016686
LED	13,5 W	I	-	80	4000	-	A/EW	-	1002 lm	269 lm	80	10	50000 h	●	301669
LED	13,5 W	I	-	80	3000	-	A/EW	-	912 lm	327 lm	80	10	50000 h	●	3016696
LED	13,5 W	I	-	80	4000	-	A/EW	-	1002 lm	269 lm	80	10	50000 h	○	301667
LED	13,5 W	I	-	80	3000	-	A/EW	-	912 lm	327 lm	80	10	50000 h	○	3016676



NIKKO+27/VV

IK06 1J xx3

LAMPHOLDER	WATTAGE	CLASS	☑	CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	CLOUR/ RAL	PART NUMBER
E27	1x60 W	I	✓	-	-	-	A/EW	-	-	-	-	-	-	●	002061
E27	1x60 W	I	✓	-	-	-	A/EW	-	-	-	-	-	-	●	002062
E27	1x60 W	I	✓	-	-	-	A/EW	-	-	-	-	-	-	○	002060



GENERAL OUTDOOR

OPTIONAL ACCESSORIES

Bracket suitable for single or twin (back to back) luminaire mounting, comprising:

- Support in painted extruded aluminium
- Wall mounting bracket with simple fix installation system, in painted die-cast aluminium

Post comprising:

- Painted extruded aluminium post, suitable for single or twin (back to back) luminaire mounting.
- Painted die-cast aluminium base plate
- Die-cast aluminium junction box with a 4-pole 4 mm² terminal suitable for loop in wiring connection.

DESCRIPTION	COLOR	PART NUMBER
NIKKO+21		
Wall bracket 21	○	000400
Wall bracket 21	●	000401
Wall bracket 21	●	000402
Post 21 H200	○	000404
Post 21 H200	●	000405
Post 21 H200	●	000406
Post 21 H550	●	000410
Post 21 H550	●	000409
Post 21 H800	○	000412
Post 21 H800	●	000413
Post 21 H800	●	000414
NIKKO+27		
Wall bracket 27	●	000421
Wall bracket 27	●	000422
Post 27 H265	○	000424
Post 27 H265	●	000425
Post 27 H265	●	000426
Post 27 H800	○	000428
Post 27 H800	●	000429
Post 27 H800	●	000430
Post 27 H1200	●	000434



B **A**

Complete unit

1A+1B = please order 2 codes


2A+1B = please order 3 codes

COMPONENTS

A luminaire


B bracket

NIKKO+21




000400
000401
000402

NIKKO+27



000421
000422



Complete unit

1A+1B = please order 2 codes

2A+1B = please order 3 codes

COMPONENTS

A luminaire

B pole

