


GUELL 2



Scan the QR-code for the latest information


■ GR-94 / Metallic grey / Textured

LED floodlight for indoor and exterior lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, tempered, flat toughened glass diffuser
- High-performance polished, oxidised, iridescence-free pure aluminium reflector (Al 99.99)
- Anti-ageing silicone sealing gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- A50/W models feature low-glare optics specifically studied for lighting schemes that require highly asymmetrical optimised distributions
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- Openable and maintainable luminaire (future-proof)
- Dimmable ballast available. Consult factory
- Other colour temperatures (CCT) and different colour rendering index (CRI) options available. Consult factory
- For integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM) consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Design by GIORGIO LODI



Church of St. George in Braida - Verona - Italy



GUELL 2 S/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
149	I	-	80	4000	S/W	-	25350	20335	■	3112391	
149	I	-	80	3000	S/W	-	24089	19324	■	3112388	
103	I	-	80	4000	S/W	-	16198	13233	■	3115110	
103	I	-	80	3000	S/W	-	15320	12830	■	3115111	-
74	I	-	80	4000	S/W	-	12148	10463	■	3115115	
74	I	-	80	3000	S/W	-	11196	10150	■	3115116	-

DALI and 5000K versions are available on web

GUELL 2 A/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
149	I	-	80	4000	A40/W	-	25350	20323	■	3112390	
149	I	-	80	3000	A40/W	-	24089	19312	■	3112387	
103	I	-	80	4000	A40/W	-	16198	13006	■	3115119	
103	I	-	80	3000	A40/W	-	15320	12619	■	3115120	
74	I	-	80	4000	A40/W	-	12148	10030	■	3115125	
74	I	-	80	3000	A40/W	-	11196	9605	■	3115126	

DALI and 5000K versions are available on web

GUELL 2 A50/W

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
80	I	-	80	4000	A50/W	-	12085	10032	■	3115103	
80	I	-	80	3000	A50/W	-	10182	9396	■	3115102	

GUELL 2 C/I

IP66 - IK07 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	PRONTO
Power LED 220-240 V 50/60 Hz											
101	I	-	80	4000	C/I	-	14552	11930	■	3115108	-
101	I	-	80	3000	C/I	-	14118	11471	■	3115107	-
72	I	-	80	4000	C/I	-	11116	9470	■	3115105	-
72	I	-	80	3000	C/I	-	10784	9105	■	3115104	-

DALI and 5000K versions are available on web

OPTIONAL ACCESSORIES

DESCRIPTION	COLOR	PART NUMBER	PRONTO
GUELL 2			
Protective grid GUELL 2		14173502	-
Connection box IP 66		14174220	-
Wall support 500 mm/19.69" GUELL 1/2	■	14173394	
Wall support 1000 mm/39.37" GUELL 1/2	■	14173494	
Single pole top support GUELL 2	■	14174094	
Double pole top support GUELL 2	■	14174194	
Reinforcing bracket GUELL 2 in painted steel. Used to fasten the floodlight with a single screw in the centre of the bracket	■	14460594	-
GUELL 2 A/W - GUELL 2 S/W			
Soft glass GUELL 2	■	14173994	-
GUELL 2 A/W			
Cover GUELL 2 Asymmetrical	■	14173694	-
Louvre GUELL 2 Asymmetrical		14173820	-
GUELL 2 S/W			
Louvre GUELL 2 Symmetrical		14173720	-
GUELL 2 C/I			
GUELL 2/C frosted glass		14476794	-

