








PA44

**Pillar Terminal Block
(12 poles)**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	750V - 41A	300V - 25A
Wire size	6.0 sqmm	14 ÷ 10AWG
Working Temperature	- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
Plastic Material	Polyamide PA6.6 natural colour, UL94 V2, GWT 960°C	
Metal Parts	Cage insert made in nickel plated brass; M3.5 Captive screw made in zinc plated steel	
Accessories	PA296 - PA228 - PA52 - PA197	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	CA02.00596	6.0 sqmm - 750V - 41A - 110°C	EN 60998-1; EN 60998-2-1
	CA02.00596	6.0 sqmm - 750V - 41A - 110°C	EN 60998-1; EN 60998-2-1
	121128	6.0 sqmm - 450V - 41A - 110°C	DIN EN 60998-1; DIN EN 60998-1/A1; DIN EN 60998-2-1 (VDE 0613)
	E76048 vol. 1 sec. 1	14 ÷ 10 AWG - 300V - 25A - 105°C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	18 ÷ 10 AWG - 300V - 25A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 44/12P	102012	200	30x20x40	11.0

DIMENSIONAL
DRAWING

