



GENERAL INFORMATION

| | |
|------------------------|----------------|
| pitch: | 7,5 mm |
| housing height: | 8,50 mm |
| housing depth: | 12.2 mm |
| dimensional class: | medium |
| wire section: | - |
| clamp opening size: | - |
| wire stripping: | - |
| operating temperature: | -40°C ÷ +130°C |

ELECTRICAL CHARACTERISTICS

| | |
|------------------|------|
| current: | 15A |
| voltage: | 500V |
| impulse voltage: | 6 kV |

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

| | |
|----------|------------|
| current: | 15A |
| voltage: | 500V |
| FILE: | CA02.04178 |



EN 61984

| |
|----------|
| 15A |
| 500V |
| 40005779 |



UL 1059

| |
|-------------------------|
| 12A factory / 12A field |
| 300V |
| E178356 |

MATERIALS

| | |
|---------------|-------------------------|
| housing: | PA - UL 94 V0 |
| screw: | n/a |
| clamp/spring: | n/a |
| terminal: | Tin-plated copper alloy |

AVAILABLE COLOURS



other colours: upon request

| poles | P/N | pcs/pack | W [Kg]* | W [Kg]* |
|-------|------------|----------|---------|---------|
| 02 | PV02-7,5-H | N/A | N/A | N/A |
| 03 | PV03-7,5-H | N/A | N/A | N/A |

| | | | | |
|----|------------|-----|-----|-----|
| 04 | PV04-7,5-H | N/A | N/A | N/A |
| 05 | PV05-7,5-H | N/A | N/A | N/A |
| 06 | PV06-7,5-H | N/A | N/A | N/A |
| 07 | PV07-7,5-H | N/A | N/A | N/A |
| 08 | PV08-7,5-H | N/A | N/A | N/A |
| 09 | PV09-7,5-H | N/A | N/A | N/A |
| 10 | PV10-7,5-H | N/A | N/A | N/A |
| 11 | PV11-7,5-H | N/A | N/A | N/A |
| 12 | PV12-7,5-H | N/A | N/A | N/A |
| 13 | PV13-7,5-H | N/A | N/A | N/A |
| 14 | PV14-7,5-H | N/A | N/A | N/A |
| 15 | PV15-7,5-H | N/A | N/A | N/A |
| 16 | PV16-7,5-H | N/A | N/A | N/A |