

NASTER D49 / D49 NASTER GROUND/WALL RECESSED / NASTER LED WALL WASHER / D49/3-LWN-WS-AL

## Product Info




<b>Item code</b>	NASTER D49 / D49/3-LWN-WS-AL
<b>Category</b>	Walk-over
<b>Environments</b>	façades and architectural works, hallway, industrial areas, railway areas, subway areas
<b>Mounting type</b>	with rough-in housing
<b>Body</b>	Corrosion resistant extruded aluminium body. Corrosion resistant die-cast aluminium end caps.
<b>Painting</b>	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
<b>Screws</b>	AISI 304 stainless steel screws.
<b>Seals</b>	Silicone Rubber.
<b>Static load</b>	2000Kg
<b>Standard Colour</b>	AL   aluminium grey
<b>Option colors</b>	GR   graphite satin finish



## Dimensions

<b>Total device width (mm)</b>	90
<b>Total device length (mm)</b>	940




## Optical System

<b>Diffuser</b>	Tempered safety glass - 8 mm thickness, mechanical and thermal shock resistant.
<b>Optical System</b>	Reflector.
<b>Beam</b>	wall washer
<b>Emission</b>	direct
<b>Reflectors</b>	Extra-pure aluminium reflector.
<b>Adjustable</b>	No



## Photometrics



## Sources

MacAdam	Step 3
Output Flux	2326 lm
Source type	LED
System power	28W
Temperature Colour	4000K CRI>80

## Electrical

Ballast type	ON-OFF.
Frequency	50-60Hz
Lifetime	50.000h L80B50 (Ta=25°C)
Line input	Internal looping facility with two H07RN-F, rubber cable section 2x1,5mm <sup>2</sup> maximum allowed current 6A. Pre-wired and tested with resin sealed watertight H07RN-F cables (for a fast and secure connection to the main power line, use ACS/CR1 connector or similar.
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No



## Optional Accessories

### Electrical



**ACS/CR1**

Fast IP68 connector 1bar (10m-1h) for cable Ø7-12mm - 3x1.5mm.



**ACS/CR6**

4 ways IP68 wiring box for cable Ø5-14mm - 3x1,5mm.

### Rough-in housing



**D49/G1**

Rough-in housing for ground/wall - stainless steel for 940mm fixture. A rough-in stainless steel housing is supplied for recessed installation, providing a sturdy installation of the fixture and space for electrical connections.