

Products /  **CASTALDI** / ERAD/C D54 / D54 ERAD/C2 / D54/F24-AL

ERAD/C D54 D54/F24-AL

TECHNICAL DATA

GENERAL



| | |
|--------------------|--|
| Item code | D54/F24-AL |
| Place installation | outdoor |
| Name | D54 ERAD/C2 / D54/F24-AL wall mounted |
| Note | Standard finish polished stainless steel finish. Class II insulation on request. |
| Standard colour | AL - aluminium grey (similar to RAL 7040) |
| Variant colour | GR - graphite satin finish (similar to RAL 7022) |
| Environments | façades and architectural works, wellness, hallway, conference hall, places of worship |




PHYSICAL

| | |
|-------------------|---|
| Installation type | wall mounted |
| Mounting type | surface |
| Screws | AISI 304 stainless steel screws. |
| Seals | Silicone Rubber. |
| Body | Steel body with polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment). |




DIMENSIONS

L: Total length device (mm) 420




OPTICAL SYSTEMS

| | |
|--------------|---------------------------------|
| Opening beam | diffused |
| Reflectors | Extra-pure aluminium reflector. |
| Diffuser | Metacrylate satin finish. |



ENERGY SAVING

This luminaire is compatible with bulbs of the energy classes:





SOURCES

| Source Type | Source Power | System Power | Source | Lamp Socket | Sources Temperature Colour | Nominal Flux | Output Flux | Source description |
|---------------------|--------------|--------------|--------|-------------|----------------------------|--------------|-------------|--------------------|
| compact fluorescent | 24W | - | TC-L | 2G11 | - | 1800 lm | - | - |

ELECTRICAL

| | |
|-----------------------|--|
| Ballast type | Electronic |
| Mounting ballast type | Integral |
| Line input | Use only (EN 60598-1) cable type H07RN-F with diameter between 8 and 10mm. |
| Voltage | 220-240V |
| Frequency | 50-60Hz |

PHOTOMETRICS



isolux distribution
on white colour wall
fixture height 2.5m
*distribuzione isolux
parete colore bianco
apparecchio h 2.5m*

isolux distribution on ground
distribuzione isolux al suolo

NORMS / DIRECTIVES

| | |
|------------|--------------------------|
| Norms | EN 60598-1, EN 60598-2-1 |
| Directives | 2014/35/UE, 2014/30/UE |

ACCESSORIES

OPTIONAL ACCESSORIES

Structural

| | |
|-----------------------|----------------------------------|
| Accessory code | D54/B24-AL |
| Technical description | Wire cover canopy. -AL ALUMINIUM |

