


KHA SLIM 220 LED C/EW




Part number	06081696
Lampholder:	LED
Light Source:	LED
Wattage:	13 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	II
Degree of protection:	IP66
IK-J-xxIP:	IK09 10J xx7
CRI:	70
Kelvin:	5000
Power factor:	$\cos\phi \geq 0,9$
Optic:	EXTRA WIDE CIRCLE REFLECTOR
Lightsource lumen output:	1899 lm
Luminaire lumen output:	592 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	30°



Description

- Luminaire for indoor and outdoor floor mount, comprising:
- Housing and cap made of AISI 316 electropolished stainless steel or powder coated aluminium, depending on versions
 - Clear UV-stabilised and impact resistant technopolymer cover
 - Extra pure polished aluminium reflectors
 - Anti-aging silicone gasket
 - Electrical connection with quick disconnect connector in PA66 without halogens and phosphorus with silver-plated copper contacts, for cables Ø 9 - Ø 14 mm
 - LED versions are manufactured with high performance LED arrays
 - Anodised extruded aluminium profile for correct dissipation of the LED light source
 - Stainless steel external screws
 - Technopolymer electrical gear support
 - Fixing rods are available as accessories for installation on cement
 - Die-cast aluminium floor mount base polyester, powder coated after chemical conversion treatment of the surface
 - KHA SLIM 220 floor installation can be done through a galvanised steel plinth to be directly buried in concrete or with a stainless steel base to be fastened to the floor with anchor bolts (included)
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

KHA SLIM



14071220

Hot dipped galvanised fixing base for recessing into concrete (suitable only for models 220/250 cm height)



14071120

AISI 316 stainless steel floor installation base (suitable only for models 220/250 cm height)