



## MIMIK 20 FLAT B




<b>Part number</b>	303750
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	24 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Asymmetric Wide Reflector
<b>Lightsource lumen output:</b>	3306 lm
<b>Luminaire lumen output:</b>	1930 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	40°




### Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
  - Flat, microprismatic tempered glass diffuser, screen printed on the inner surface for MIMIK FLAT series
  - Silicone gasket
  - LED versions include 220/240 V 50/60 Hz safety transformer
  - "MIMIK fixtures are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - Double-emission (B) versions are equipped with two lights in order to provide upward and downward emission
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### MIMIK FLAT B



310442  
FLAT B Customising ring / Facade  
Accessory