

# INSERT+ ZERO




<b>Part number</b>	304108
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	5 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK08 5J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	ASYMMETRIC MEDIUM REFLECTOR
<b>Lightsource lumen output:</b>	511 lm
<b>Luminaire lumen output:</b>	125 lm
<b>L:</b>	L90
<b>B:</b>	B10
<b>Lifetime:</b>	36000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	45°



## Description

- Wall recessed luminaire, for indoor and outdoor comprising:
- Polyester powder coated die-cast aluminium housing
  - Diffuser in flat glass, internally frosted
  - EPDM gasket
  - Stainless steel locking screws
  - 503 standard recessed box included in the product
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - The fitting is suitable for through-wiring
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

