


QUASAR 30 TECH EM/3P




Part number	304196
Lampholder:	LED+LED
Light Source:	LED / LED
Wattage:	23 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	ASYMMETRIC MEDIUM REFLECTOR
Lightsources lumen output:	2276 lm
Luminaire lumen output:	1350 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	0°
Ta MAX luminaire:	25°



Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
 - Flat microprismatic glass diffuser internally pattern for TECH versions
 - Reflector in satin finish pure aluminium (Al 99.98)
 - Silicone gasket
 - EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
 - EM/3P LED versions feature an additional LED that is used for emergency lighting
 - Ni-Cd 3,6 V, 4 Ah batteries, 3-hour maintained, 24 hours recharge time
 - 3 hours
 - Powder polyester painting process optimized against UV rays in 13 different steps
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

