

KOA LINE STR/PC S/EW




Part number	06243694
Lampholder:	LED
Light Source:	LED
Wattage:	112 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK08 9J xx5
CRI:	85
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	13350 lm
Luminaire lumen output:	10013 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-25°
Ta MAX luminaire:	25°




Description

- Range of indoor and outdoor LED fixtures, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Opal polycarbonate diffuser
 - Anti-aging silicone gasket with high resiliency
 - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables Ø 9 - Ø 12 mm
 - Dimmable DALI
 - Light beam obtained by the combination of multiple LED modules
 - Galvanised steel suspension hooks
 - Stainless steel external screws
 - In order to allow the use of these devices in various installation situations - on the wall, the ceiling, or a post - a wide range of accessories is available.
 - In order to guarantee resistance to wind forces, we suggest using the installation systems available as accessories for outdoor spaces.
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings




OPTIONAL ACCESSORIES

KOA LINE



14471694
KOA LINE mounting bracket



14471894
Pair of AISI 304 stainless steel
mounting brackets KOA LINE




14471494
Single pole top Ø 60-76 mm support
KOA LINE



14471594
Double pole top Ø 60-76 mm KOA
LINE support



14471794
Pair of mounting brackets with
stainless steel clamps for Ø33-42mm
pole / rail installation



14006902
Galvanized steel protection grid, for
ceiling mounting