



# MIMIK 30 CP/T3




<b>Part number</b>	303848
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	30 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	70
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	PEDESTRIAN AND CYCLE REFLECTOR Type 3
<b>Lightsource lumen output:</b>	4160 lm
<b>Luminaire lumen output:</b>	2558 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	25°



## Description

- Indoor and outdoor wall-mount fixture, including:
- Polyester powder coated die-cast aluminium housing
  - Flat, transparent, tempered glass diffuser, screen printed on the inner surface for MIMIK series
  - Silicone gasket
  - LED versions include 220/240 V 50/60 Hz safety transformer
  - "MIMIK fixtures are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

