

FOCUS+3 C/W



Part number	305237
Lampholder:	LED
Light Source:	LED
Wattage:	50 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK09 10J xx7
CRI:	70
Kelvin:	3000
Power factor:	$\cos\phi \geq 0,9$
EEL:	A2
Optic:	Wide Circle Intensive Reflector
Optic Beam:	56°
Lightsources lumen output:	5040 lm
Luminaire lumen output:	3449 lm
L:	L70
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	30°




Description


LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast painted aluminium housing and trim
- Adjustable mounting bracket made of die-cast aluminium, painted
- Extra-clear flat tempered glass diffuser with internal screen printing
- Circular optic
- High power LEDs with next generation high intensity light beam
- Silicone gasket
- Stainless steel locking screws
- Cable gland M20x1.5 for cables Ø 7- Ø 12 mm
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

FOCUS+3



14099896
Gliding support made of painted
aluminium for the installation on Ø 60
mm posts



14099696
Gliding support made of painted
aluminium for the installation on Ø 90
mm posts



311043
Fixing bracket