

FOCUS+3 A/M




| | |
|----------------------------------|------------------------------------|
| Part number | 305241 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 50 W |
| Finish: | AN-96 / Anthracite gray / Textured |
| Insulation class: | I |
| Degree of protection: | IP66 |
| IK-J-xxIP: | IK09 10J xx7 |
| CRI: | 70 |
| Kelvin: | 3000 |
| Power factor: | COSφ ≥ 0,9 |
| EEL: | A2 |
| Optic: | ASYMMETRIC MEDIUM REFLECTOR |
| Optic Beam: | 10° |
| Lightsource lumen output: | 5040 lm |
| Luminaire lumen output: | 3409 lm |
| L: | L70 |
| B: | B10 |
| Lifetime: | 60000 h |
| Ta MIN luminaire: | -20° |
| Ta MAX luminaire: | 30° |




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast painted aluminium housing and trim
 - Adjustable mounting bracket made of die-cast aluminium, painted
 - Extra-clear flat tempered glass diffuser with internal screen printing
 - Asymmetrical optic
 - High power LEDs with next generation high intensity light beam
 - Silicone gasket
 - Stainless steel locking screws
 - Cable gland M20x1.5 for cables Ø 7- Ø 12 mm
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

FOCUS+3



14099896
Gliding support made of painted aluminium for the installation on Ø 60 mm posts



14099696
Gliding support made of painted aluminium for the installation on Ø 90 mm posts



311043
Fixing bracket