


## NORMA+ 150 CL




|                                  |                                  |
|----------------------------------|----------------------------------|
| <b>Part number</b>               | 305946                           |
| <b>Lampholder:</b>               | LED                              |
| <b>Light Source:</b>             | LED                              |
| <b>Wattage:</b>                  | 60 W                             |
| <b>Finish:</b>                   | GR-RAL7035 / Grey RAL7035 / Matt |
| <b>Insulation class:</b>         | I                                |
| <b>Degree of protection:</b>     | IP65                             |
| <b>IK-J-xxIP:</b>                | IK09 15J xx7                     |
| <b>CRI:</b>                      | 80                               |
| <b>Kelvin:</b>                   | 4000                             |
| <b>Power factor:</b>             | $\text{COS}\phi \geq 0,9$        |
| <b>Optic:</b>                    | SYMMETRIC EXTRA WIDE REFLECTOR   |
| <b>Lightsource lumen output:</b> | 9060 lm                          |
| <b>Luminaire lumen output:</b>   | 7556 lm                          |
| <b>L:</b>                        | L80                              |
| <b>B:</b>                        | B10                              |
| <b>Lifetime:</b>                 | 44000 h                          |
| <b>Ta MIN luminaire:</b>         | -20°                             |
| <b>Ta MAX luminaire:</b>         | 45°                              |




### Description

- Weatherproof luminaire with LED light source, comprising:
- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
  - Technopolymer end caps
  - Anti-aging silicone gasket
  - Polycarbonate bushing for the power connection with bayonet opening without utensils.
  - Cable gland M20x1.5 for cables  $\varnothing 10$ - $\varnothing 14$  mm
  - Luminaire complete with through wiring for power supply to a continuous row
  - Light beam obtained by the combination of multiple LED modules
  - Aluminium heat dissipation system
  - Stainless steel springs for quick ceiling mount
  - Supplied with anti-vacuum valve
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### NORMA+ 150



14431995

Galvanized steel protection grills, to  
be fixed on ceiling