

NOTTURNO 1500



Part number	304925
Lampholder:	LED
Light Source:	LED
Wattage:	60 W
Finish:	GR-11 / Anodised grey / Matt
Insulation class:	III
Degree of protection:	IP66
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic Beam:	13°x36°
Lightsource lumen output:	6064 lm
Luminaire lumen output:	4571 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-30°
Ta MAX luminaire:	50°




Description


Indoor and outdoor wall-mount fixture, including:

- Extruded anodised aluminium housing
- Tempered glass diffuser, printed
- Class III
- Shank connection in Stainless Steel AISI 304
- Elliptical lens
- Aluminium heat sink
- For the installation of the product must be used the appropriate brackets available as an accessory
- On request, versions with DALI dimming
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



CONTROL GEAR

NOTTURNO




310543
Power Supply Unit L1000/1500

MANDATORY ACCESSORIES

NOTTURNO



310523
Bracket NOTTURNO (nr. 2)



310524
Bracket (nr. 2)



310978
NOTTURNO Telescopic bracket



310981
NOTTURNO ground support bracket