

GUELL ZERO A/W




Part number	306521
Lampholder:	LED
Light Source:	LED
Wattage:	28 W
Finish:	BK-RAL9005 / Black RAL9005 / Glossy
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	3382 lm
Luminaire lumen output:	2575 lm
L:	L70
B:	B10
Lifetime:	150000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
 - Very high performance asymmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - Powder coated steel bracket
 - Complete with 1 metre of cable H05RN-F 3G1 mm²
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

GUELL ZERO



14453380
500 mm arm completes with
connection base GUELL ZERO



14453480
1000 mm arm completes with
connection base GUELL ZERO