

Products /  **CASTALDI** / TARZAN D17 / D17 TARZAN/N / D17/N9LWW

TARZAN D17 D17/N9LWW

TECHNICAL DATA

GENERAL



Item code	D17/N9LWW
Place installation	outdoor
Name	D17 TARZAN/N / D17/N9LWW underwater
Note	Submerged operation - max allowed depth 10m.
Standard colour	B - white
Environments	urban landscape, wellness, hallway




PHYSICAL

Installation type	underwater
Seals	Silicone Rubber.
Body	Injection moulded high stress resistant composite technopolymer niche and floodlight.




DIMENSIONS

D: Total diameter device (mm)	206
Built-in shaped	Round
Diameter built-in (mm)	140
Built-in depth (mm)	140




OPTICAL SYSTEMS

Opening beam	roto-symmetrical
Optical System	Safety tempered glass.
Reflectors	Extra-pure aluminium reflector.



ENERGY SAVING

This luminaire contains built-in LED lamps
The lamps cannot be changed in the luminaire



SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature Colour	Nominal Flux	Output Flux	Source description
LED	9W	-	LED	-	3000K	383 lm	328 lm	-

ELECTRICAL

Ballast type	Electronic
Mounting ballast type	Independent
Line input	Pre-wired, with sealed 5,5m long cable in compliance with HD22-16.S1/AD8, cable 2x1,5mm ² and flexible protective sheath.
Voltage	12V

NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-18
Directives	2014/35/UE, 2014/30/UE


ACCESSORIES

OPTIONAL ACCESSORIES

Electrical


Accessory code CV/1221

Technical description
Power supply neoprene rubber cable approved for submerged operation 2x2,5mm². Sold per meter.



Accessory code D17/G25


Technical description
Sheathed cable. 2x2,5mm² power supply rubber cable approved for submerged operation (HD22-16.S1/AD8) complete with heavy flexible protection sheath Ø25mm. Sold per meter.



Structural

Accessory code D17/GZ38

Technical description
Gasket for prefabricated pools with vinyl coating. When there are prefabricated pools with vinyl coating with the structure below not perfectly smooth (for example pool walls in polyester resin fiber glass reinforced) it is necessary to place, between the rough wall and the vinile coating a sealing gasket to avoid water infiltrations under the coating. The GZ38 gasket in soft para rubber of fair thickness is suitable to that purpose.



Accessory code D17/CH

Technical description
Locking key for floodlight - niche - TZ box - mandatory for mounting and maintenance operations. The use of the locking key D17/CH is necessary to open and close the floodlight correctly in case of re-lamping. It is also necessary for any maintenance operation on the connection and transformer box TZ box.

