


INSERT+ 1



Part number	304119
Lampholder:	LED
Light Source:	LED
Wattage:	7 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
Optic:	ASYMMETRIC MEDIUM REFLECTOR
Lightsource lumen output:	850 lm
Luminaire lumen output:	275 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-10°
Ta MAX luminaire:	35°




Description


Wall recessed luminaire, for indoor and outdoor comprising:

- Polyester powder coated die-cast aluminium housing
- Diffuser in flat glass, internally frosted
- EPDM gasket
- External electrical connection with sealed plug-socket QUICK, complete with cable
- Electrical connector for wires Ø 7 - Ø 12 mm
- Stainless steel locking screws
- The fixture requires recessed fixing box which must be ordered separately
- The recessed box is equipped with a removable cover and provided with two spirit levels to facilitate the installation process
- Powder polyester painting process optimized against UV rays in 13 different steps
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



MANDATORY ACCESSORIES

INSERT+ 1



310475
Recessed box INSERT+ 1

OPTIONAL ACCESSORIES

INSERT+ 1



310478
Adaptor INSERT+ 1