


# MULTI+ 40 PC EM/3P




<b>Part number</b>	304139
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	19.5 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	II
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK10 20J xx9
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	3121 lm
<b>Luminaire lumen output:</b>	1502 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	0°
<b>Ta MAX luminaire:</b>	30°




## Description

- Wall and ceiling mounting luminaire for indoor and outdoor, comprising:
- Technopolymer housing
  - Opal diffuser manufactured from technopolymer, 960°C glow wire test rated
  - Class II
  - Silicone gasket
  - Through-wiring possible
  - Stainless steel, anti-tamper locking screws
  - EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
  - 3 hours
  - Max 20 mm diameter for cable/conduit entry
  - Supplied with SMD self-heat dissipating power LED metal core board: FUTURE-PROOF™
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings



## OPTIONAL ACCESSORIES

### MULTI+ 40 PC



310514  
Tool TORX