


## MULTI+ 30 PC




|                                   |                                |
|-----------------------------------|--------------------------------|
| <b>Part number</b>                | 304161                         |
| <b>Lampholder:</b>                | LED                            |
| <b>Light Source:</b>              | LED                            |
| <b>Wattage:</b>                   | 16 W                           |
| <b>Finish:</b>                    | WH-87 / White / Textured       |
| <b>Insulation class:</b>          | II                             |
| <b>Degree of protection:</b>      | IP65                           |
| <b>IK-J-xxIP:</b>                 | IK10 20J xx9                   |
| <b>CRI:</b>                       | 80                             |
| <b>Kelvin:</b>                    | 4000                           |
| <b>Power factor:</b>              | $\cos\phi \geq 0,9$            |
| <b>Optic:</b>                     | SYMMETRIC EXTRA WIDE REFLECTOR |
| <b>Lightsources lumen output:</b> | 2447 lm                        |
| <b>Luminaire lumen output:</b>    | 1292 lm                        |
| <b>L:</b>                         | L80                            |
| <b>B:</b>                         | B10                            |
| <b>Lifetime:</b>                  | 60000 h                        |
| <b>Ta MIN luminaire:</b>          | -20°                           |
| <b>Ta MAX luminaire:</b>          | 30°                            |




### Description

- Wall and ceiling mounting luminaire for indoor and outdoor, comprising:
- Technopolymer housing
  - Opal diffuser manufactured from technopolymer, 960°C glow wire test rated
  - Class II
  - Silicone gasket
  - Through-wiring possible
  - Stainless steel, anti-tamper locking screws
  - Max 20 mm diameter for cable/conduit entry
  - Supplied with SMD self-heat dissipating power LED metal core board: FUTURE-PROOF™
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## OPTIONAL ACCESSORIES

### MULTI+ 30 PC



310514  
Tool TORX