


NORMA+ 120 CL



Part number	305998
Lampholder:	LED
Light Source:	LED
Wattage:	25 W
Finish:	GR-RAL7035 / Grey RAL7035 / Matt
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK09 15J xx7
CRI:	80
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	3775 lm
Luminaire lumen output:	3002 lm
L:	L80
B:	B10
Lifetime:	44000 h
Ta MIN luminaire:	5°
Ta MAX luminaire:	40°




Description


Weatherproof luminaire with LED light source, comprising:

- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
- Technopolymer end caps
- Anti-aging silicone gasket
- Polycarbonate bushing for the power connection with bayonet opening without utensils.
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Luminaire complete with through wiring for power supply to a continuous row
- Light beam obtained by the combination of multiple LED modules
- Aluminium heat dissipation system
- Stainless steel springs for quick ceiling mount
- Version complete with emergency device that can operate on battery for 1 hour. Product can be used for general or emergency lighting
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

NORMA+ 120



14430995

Galvanized steel protection grills, to
be fixed on ceiling