

GUELL ZERO KIT S/M



Part number	306540
Lampholder:	LED
Light Source:	LED
Wattage:	28 W
Finish:	WH-RAL9010 / White RAL9010 / Glossy
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	3000
Power factor:	COS ϕ $\geq$ 0,9
Optic:	SYMMETRIC MEDIUM REFLECTOR
Lightsource lumen output:	3295 lm
Luminaire lumen output:	2439 lm
L:	L70
B:	B10
Lifetime:	150000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°




Description

LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
- Extra pure polished aluminium reflectors
- Stainless steel external screws
- Stainless steel locking springs for the glass
- Powder coated steel bracket
- Complete with 1 metre of cable H05RN-F 3G1 mm²
- Versions of GUELL ZERO KIT are complete with 0.5 m arm with integrated connection box, suitable for through wiring
- DETEK versions with a passive infrared motion detector with automatic ignition
- 3000 K and 5000 K available upon request
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

