

DLSB185 LED OPAL COVER - 95 MM




Part number	818711234001
Lampholder:	LED
Light Source:	LED
Wattage (W):	13 W
Finish / RAL:	White RAL9016
Insulation class:	I
Degree of protection:	IP 20
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
EEL:	A2
Optic:	EXTRA WIDE CIRCLE REFLECTOR (=>75°)
Optic Beam:	2 x 46°
Lightsource lumen output:	1700 lm
Luminaire lumen output:	1190 lm
Lifetime:	50000 h
Percent lumen depreciation:	L80



Description

- Round and modular downlight with various expansion options
- Conclusive continuation of the classic product in innovative LED technology
- Designed for versatile applications and planning variations
- Is a design tool that is characterized by its unambiguous conception
- Ceiling rings, white cones and a white, opaque disc enable discrete integration in the ceiling
- The luminaire can be operated at different power settings
- Universal die-cast aluminium part combines all functions: LED heat sink, anti-glare ring, ceiling attachment and power connection unit
- Modular reflector made of injection-moulded ABS in white with lightproof connection to the LED module
- Extremely easy installation and efficient mounting
- High quality thermal management system through die-cast aluminium cooling element with FAST (Flexible Air Stream Technology)
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Rated LED service life of 50,000 hrs before luminance drops to 70 % (L80B10 50.000h)
- With direct light distribution
- Even illumination throughout the entire light emission surface

PHOTOMETRIC DATA



TECHNICAL DRAWINGS

