

DLSB185 LED OPAL COVER - 95 MM




Part number	818711264001
Lampholder:	LED
Light Source:	LED
Wattage (W):	13 W
Finish / RAL:	White RAL9016
Insulation class:	I
Degree of protection:	IP 20
Kelvin:	4000
Power factor:	COS ϕ $\geq$ 0,9
EEL:	A1
Optic:	EXTRA WIDE CIRCLE REFLECTOR ($\Rightarrow$ 75°)
Optic Beam:	2 x 46°
Lightsource lumen output:	1700 lm
Luminaire lumen output:	1190 lm
Lifetime:	50000 h
Percent lumen depreciation:	L80



Description

- Round and modular downlight with various expansion options
- Conclusive continuation of the classic product in innovative LED technology
 - Designed for versatile applications and planning variations
 - Is a design tool that is characterized by it's unambiguous conception
 - Ceiling rings, white cones and a white, opaque disc enable discrete integration in the ceiling
 - The luminaire can be operated at different power settings
 - Universal die-cast aluminium part combines all functions: LED heat sink, anti-glare ring, ceiling attachment and power connection unit
 - Modular reflector made of injection-moulded ABS in white with lightproof connection to the LED module
 - Extremely easy installation and efficient mounting
 - High quality thermal management system through die-cast aluminium cooling element with FAST (Flexible Air Stream Technology)
 - Colour tolerance according to MacAdam $\leq$ 3 SDCM
 - Rated LED service life of 50,000 hrs before luminance drops to 70 % (L80B10 50.000h)
 - With direct light distribution
 - Even illumination throughout the entire light emission surface

PHOTOMETRIC DATA



TECHNICAL DRAWINGS

