



THB.381.L3E

MADE IN ITALY

TH381 - micro-Plug&Socket connector IP68/IP69K



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP68/IP69K Plug&Socket circular connectors
Product name (Series)	TH381 - micro-Plug&Socket connector IP68/IP69K
Product configuration	Connettore Spina <i>* Fixing nut included in the kit.</i>
Thread	M11
Panel thickness min. - max.	1.0 mm - 4.0 mm
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 14 mm x 21 mm x 54 mm

ELECTRICAL CHARACTERISTICS

Number of poles	3
Contact marking	L-N-E
Type of connection	Grano (M2 - max. 0.2 Nm)
Operating current	10A AC (max. 1A DC)
Operating voltage	400V AC/DC (48V DC)
Impulse withstand voltage	4KV

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (30m/1h)/IP69K
Protection against impact (IK)	IK06
Corrosion resistance	Salt mist test : EN60068-2-11:2000
Connection and disconnection cycles	100 cycles

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.25 mm ² - 1.0 mm ²
---	--

MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 (f1) - GWT 960°C
Connector housing	PA66 GF UL94 V0 (f1) - GWT 960°C
Cable gland	PA66 GF UL94 V2 - GWT 850°C
Sealing	TPE
Grommets	TPE
Contacts	CuZn (silver plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free - Silicone Free
T marking	T 125°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

INDUSTRY STANDARDS

Standard number	EN 61984:2009 / EN61535
-----------------	-------------------------

PACKAGING INFORMATION



Packaging method componenti non assemblati

Quantity (product/box) 200 pz

Box dimension 290x187x156mm