



## THB.402.C1F.R

TH402 - Circular junction connector 3 ways type "T" IP68

MADE IN ITALY



KIT



IP68



### GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEETUBE® - In-line and junction circular connectors IP68/IP69K
Product name (Series)	TH402 - Giunto circolare di derivazione a 3 vie tipo "T" IP68
Product configuration	In-line joint connector
Type of Fixation	With quick-fix mounting clip * Mounting clip to be ordered separately (code 6000302CC).
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 32 mm x 91 mm x 121 mm

### ELECTRICAL CHARACTERISTICS

Number of poles	5
Contact marking	1 - 2 - L - N - E
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 32A
Operating voltage	max. 450V AC

**i** Contact our Customer Service for availability of other markings.

### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (20m, 1h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

**i** Contact our Customer Service for availability of products with different IP and IK protection degrees.

### CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup>
Wire cross-section min. - max. (Solid cable)	0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup>
Cable diameter min. - max.	6.0 mm - 13.5 mm (main cable) / 6.0 mm - 13.5 mm (branch cable) * Accessories e riduzioni per cavi incluse nella confezione. Closure cap included in the kit.

### MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free
T marking	T 85°C

### DATASHEETS

- Techno TEETUBE TH402 PDF • 1 MB

### INSTALLATION INSTRUCTIONS

- Guidelines Installation PDF • 753 KB
- IST TH390T-402T v01 techno PDF • 1 MB

### CERTIFICATIONS AND TEST REPORTS

- TEETUBE CA0203009-T Y -2085  
PDF • 388 KB
- CE-TH402 DOC • 142 KB

### DRAWINGS

- THB402C2ESTEP  
• 3 MB •  CONFIDENTIAL DOCUMENT



Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 250

**i** Contact our Customer Service for more information on additional tests and approvals.

#### INDUSTRY STANDARDS

Standard number	EN 60998-1:2004
-----------------	-----------------

#### PACKAGING INFORMATION

Packaging method	single packed unit
Quantity (product/bag)	1 product/bag
Quantity (product/box)	30 bags/box
Unit weight	106,8 gram/bag
Box dimension	400 x 230 x 400

**i** Accessories and installation instructions included in the kit.