



FUSIBILI PER SPINE INGLESI

Fuses for english plugs | Fusibles pour fiches anglaises

Dimensioni

6,3x25,4 mm (GF180xx)

5x19 mm (GF170xx)

Caratteristica

F= rapidi

Tensione

240 V (GF180xx)

250 V (GF170xx)

Capacità di rottura

6.000 A (GF180xx)

1000 A (GF170xx)

Corpo

Ceramica

Capsule

Argento

Cod. omologazione

BUSS TDC 180

BUSS TDC 17

Norme riferimento

BS 1362 - IEC 269-3A

BS 646

Dimensions

6,3x25,4 mm (GF180xx)

5x19 mm (GF170xx)

Characteristic

F= fast

Voltage

240 V (GF180xx)

250 V (GF170xx)

Breaking capacity

6.000 A (GF180xx)

1000 A (GF170xx)

Body

Ceramic

Caps

Silver

Approval code

BUSS TDC 180

BUSS TDC 17

Standards

BS 1362 - IEC 269-3A

BS 646

Dimensions

6,3x25,4 mm (GF180xx)

5x19 mm (GF170xx)

Caractéristique

F= rapides

Tension

240 V (GF180xx)

250 V (GF170xx)

Pouvoir de coupure

6.000 A (GF180xx)

1000 A (GF170xx)

Corps

Céramique

Embouts

Argent

Code d'homologation

BUSS TDC 180

BUSS TDC 17

Normes

BS 1362 - IEC 269-3A

BS 646



pag. 31



TEMPI DI FUSIONE | Time current | Temps de fusion

Corrente nominale In Rated current <i>Courant nominal</i>	Corrente di prova Test current <i>Courant d'essai</i>		
	1,0xIn	1,6xIn	1,9xIn
1 A - 13 A	1000 h min	30 min min	30 min max

Corrente nominale Rated current <i>Courant nominal</i>	Codice Code <i>Code</i>	Dimensione Dimension <i>Dimension</i>	Colore Colour <i>Couleur</i>
1 A	GF 18001	6,3x25,4	■
2 A	GF 18002	6,3x25,4	■
3 A	GF 18003	6,3x25,4	■
5 A	GF 18005	6,3x25,4	■
7 A	GF 18007	6,3x25,4	■
10 A	GF 18010	6,3x25,4	■
13 A	GF 18013	6,3x25,4	■
1 A	GF 17001	5x19	■
2 A	GF 17002	5x19	■
3 A	GF 17003	5x19	■
5 A	GF 17005	5x19	■



1000 pz
1000 pcs
1000 pces



pronta
in stock
en stock



60 giorni
60 days
60 jours