

TERMINAL BLOCKS FOR P.C.B. WIRE PROTECTION

MORSETTI PER C.S. LINGUETTA

BLOCS DE JONCTION C.I. LANGUETTE

PRINTKLEMMEN DRAHTSCHUTZ

Pitch Paso	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Rated Voltage Tensione nominale	V
Rated Current Intensità nominale	Rated Current Corrente nominale	A
Types of cables Type di cavo Type de conducteur	Types of cables Type di cavo Type de conducteur	mm ² AWG
Nominal cross section Sezione nominale Section nominale	Nominal cross section Sezione nominale Section nominale	mm ² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	Stripping length Lunghezza spelatura Longueur de dénudage	mm
Torque Coppia di serraggio Couple de serrage	Torque Coppia di torsione Drehmoment	Nm
Temperature Temperatura Température	Temperature Temperatura Température	°C
Housing Corpo isolante Corps isolant	Housing Corpo isolante Corps isolant	
Screw Vite Vis	Screw Vite Vis	mm

IMQ	EN60998
VDE	EN60998
cUL	UL1059 + C22.2 n°158

Poles Pôles Colours Couleurs	Poles Pôles Colours Couleurs	X
Other information Autres données	Other information Autres données	Y
		D/A2

How to order Riferimento di comando Bestellreferenz	How to order Riferimento di comando Bestellreferenz	
CZZ 5 / X SQ Y N...	CZZ 5 / X SQ Y N...	
Type Pitch Poles Version Colors Printing	Type Pitch Poles Version Colors Printing	
Typo Passo Poli Versione Colori Numerazione	Typo Passo Poli Versione Colori Numerazione	
Type Pas Pôles Version Couleur Marquage	Type Pas Pôles Version Couleur Marquage	
Typ Rastermaß Polzahl Version Farben Bedruckung	Typ Rastermaß Polzahl Version Farben Bedruckung	

* SQ Version = Horizontal version

CZZ

CZZ..SQ*

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/24



CZZ

CZZ..SQ*

Single block - Blocco unico
Monobloc - Einzelblock


Poles - Poli - Pôles - Polzahl

2/12




5		
250		
24		
		
0,5 ÷ 4 30 ÷ 14	0,5 ÷ 2,5 30 ÷ 14	0,5 ÷ 2,5 30 ÷ 14
7		
0,5	/	4
85		
PC - UL 94 V0		
M3		
0,6 x 3,5		
		
V	A	mm ² /AWG
450	24	0,5 ÷ 2,5
450	24	0,5 ÷ 2,5
300	16	24 ÷ 14

min 2 - max 24	min 2 - max 12
GR / on demand NE	GR / on demand NE
D/A2	D/A2



10		
500		
24		
		
0,5 ÷ 4 30 ÷ 14	0,5 ÷ 2,5 30 ÷ 14	0,5 ÷ 2,5 30 ÷ 14
7		
0,5	/	4
85		
PC - UL 94 V0		
M3		
0,6 x 3,5		
		
V	A	mm²/AWG
750	24	0,5 ÷ 2,5
750	24	0,5 ÷ 2,5
300	16	24 ÷ 14

min 2 - max 12	min 2 - max 24
GR / on demand NE	GR / on demand NE
D/A2	D/A2



CBL

Single block - Blocco unico
Monobloc - Einzelblock


Poles - Poli - Pôles - Polzahl

2/24



5		
250		
24		
		
0,5 ÷ 4 30 ÷ 12	0,5 ÷ 2,5 30 ÷ 12	0,5 ÷ 2,5 30 ÷ 12
7	7	7
0,5	/	4
85		
PC - UL 94 V0		
M2,5		
0,6 x 3,5		
		
V	A	mm²/AWG
250	24	0,2 ÷ 2,5
250	24	0,2 ÷ 2,5
300	18	30 ÷ 12

min 2 - max 24	min 2 - max 12
GR / on demand NE	GR / on demand NE
D/A2	D/A2



CBL

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/12



10		
500		
24		
		
0,5 ÷ 4 30 ÷ 12	0,5 ÷ 2,5 30 ÷ 12	0,5 ÷ 2,5 30 ÷ 12
7		
0,5	/	4
85		
PC - UL 94 V0		
M2,5		
0,6 x 3,5		
		
V	A	mm²/AWG
750	24	0,2 ÷ 2,5
750	24	0,2 ÷ 2,5
300	18	30 ÷ 12

min 2 - max 12	min 2 - max 24
GR / on demand NE	GR / on demand NE
D/A2	D/A2

