



## Single-deck terminal block - Right side - Pitch 10mm - 2 poles

### GENERAL INFORMATION

pitch:	10 mm
housing height:	15,30 mm
housing depth:	9.5 mm
dimensional class:	medium
wire section:	2.5 mm <sup>2</sup> / 14 AWG
clamp opening size:	2.7 × 2.7 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	750V
test voltage:	3 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

### APPROVALS DATA



EN 60998-1

current:	16A
voltage:	750V
wire section:	2.5mm <sup>2</sup>
torque:	0.4Nm
FILE:	CA02.01614



-  
-  
-  
-  
-



UL 1059  
15A factory / 15A field  
300V  
14÷30AWG  
4.5Lb-in  
E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickeled copper alloy
terminal:	Tin-plated copper alloy

### AVAILABLE COLOURS



other colours: upon request