

FEMALE PLUG
SCREWLESS

CONNETTORI FEMMINA
MOLLA

CONNECTEURS FEMELLE
RESSORT

STECKERTEIL
FEDERKRAFT

Pitch Paso	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Tensione nominale Bemessungsspannung	V
Rated Current Intensità nominale	Corrente nominale Bemessungsstrom	A
Types of cables Type(s) de conducteur	Tipo cavo Leitungs-typen	mm ² AWG
Nominal cross section Sezione nominale Nennquerschnitt		mm mm
Stripping length Lunghezza spelatura Longueur de dénudage		
Temperature Temperatura	Temperatura Temperatur	°C
Housing Corpo isolante	Corpo isolante Isolierrkörper	
IMQ	EN61984	
VDE	EN61984	
cUL	UL1059 + C22.2 n°158	
Poles Pôles	Pol Polzahl	X
Colours Colori	Colori Farben	Y
Other information Autres données	Altre dati Weitere Informationen	P.


How to order Référence de commande	Ordinazione Bestellnummer
MRT38 P7.62 / X	FV V01 Y N...
Type Pitch Poles Version Colors Printing	Type Passo Pol Versione Colori Numerazione
Type Paso Pol Versione Colori Marquage	Type Rastermaß Polzahl Version Farben Bedruckung

MRT38..FV V01

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pol - Pôles - Polzahl


2/10



7,62		
500		
12		
		
0,2 ÷ 1,5 24 ÷ 16	0,2 ÷ 1,5 24 ÷ 16	0,2 ÷ 1,5 24 ÷ 16
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
500	12	0,2 ÷ 1,5
500	12	0,2 ÷ 1,5
300	8	24 ÷ 16

min 2 - max 10
VE / on demand GR GR1 NE AR BL RO GI
D/B2




MRT30

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pol - Pôles - Polzahl


2/24



5 - 5,08		
300 (250 V 13 + 24 POLES)		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
300	18	0,2 ÷ 2,5
300	18	0,2 ÷ 2,5
300	14	24 ÷ 14

min 2 - max 24
VE / on demand GR GR1 NE AR BL RO GI
D/B2



MRT30..FV

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pol - Pôles - Polzahl


2/20



5 - 5,08		
300 (250 V 13 + 24 POLES)		
18		
		
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
300	18	0,2 ÷ 1,5
300	18	0,2 ÷ 1,5
300	14	24 ÷ 14

min 2 - max 20
VE / on demand GR GR1 NE AR BL RO GI
D/B2




MRT30

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pol - Pôles - Polzahl


2/12



10 - 10,16		
600		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
600	18	0,2 ÷ 1,5
600	18	0,2 ÷ 1,5
300	14	24 ÷ 14

min 2 - max 12
VE / on demand GR GR1 NE AR BL RO GI
D/B2



MRT30..FV

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pol - Pôles - Polzahl

2/10



10 - 10,16		
600		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
600	18	0,2 ÷ 1,5
600	18	0,2 ÷ 1,5
300	14	24 ÷ 14

min 2 - max 10
VE / on demand GR GR1 NE AR BL RO GI
D/B2

