

MALE PLUG
SCREWLESS
CONNETTORI MASCHIO
A MOLLA
CONNECTEURS MÂLE
RESSORT
STECKERTEIL INVERTIERT
(STIFTKONTAKT)
FEDERKRAFT

Pitch Passo	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Tensione nominale Bemessungsspannung	V
Rated Current Intensità nominale	Corrente nominale Bemessungsstrom	A
Types of cables Type di conduttore	Tipo cavo Leitungs-typen	mm ² AWG
Nominal cross section Sezione nominale	Nennquerschnitt	mm ² AWG
Stripping length Lunghezza spelatura	Abschleiflänge	mm
Temperature Temperatura	Temperatura	°C
Housing Corpo isolante	Corpo isolante Isolierrkörper	

IMQ	EN61984
VDE	EN61984
cUL	UL1059 + C22.2 n°158


Poles Pôles Polen Póles Póles	Pol Polzahl Póles Póles Póles	X
Colours Colori Couleurs	Colori Farben Couleurs	Y
Other information Altre dati Autres données	Altre informazioni Weitere Informationen	P.

How to order Riferimento di comando	Ordinazione Bestellnummer
MRT40 P5.08 / X	... Y N...
Type Pitch Poles Version Colors Printing	Type Passo Póles Versión Colori Numerazione
Type Passo Póles Versión Colori Numerazione	Type Passo Póles Versión Colori Numerazione
Type Passo Póles Versión Colori Numerazione	Type Passo Póles Versión Colori Numerazione

MRT40
Single block - Blocco unico
Monobloc - Einzelblock

Poles - Póles - Póles - Polzahl


2/16



5,08		
300		
18		
		
0.2 + 2.5 24 ÷ 14	0.2 + 2.5 24 ÷ 14	0.2 + 2.5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
300	18	0.2 + 2.5
300	18	0.2 + 2.5
300	14	24 + 14


min 2 - max 16
VE / on demand GR GR NE AR BL RO G
D/B5



MRT40..A
Single block - Blocco unico
Monobloc - Einzelblock

Poles - Póles - Póles - Polzahl


2/16



5.08		
300		
18		
		
0.2 + 2.5 24 + 14	0.2 + 2.5 24 + 14	0.2 + 2.5 24 + 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
300	18	0.2 + 2.5
300	18	0.2 + 2.5
300	14	24 + 14

min 2 - max 16
VE / on demand GR GR NE AR BL RO G
D/B5



MRT40..FV
Single block - Blocco unico
Monobloc - Einzelblock

Poles - Póles - Póles - Polzahl


2/16



5,08		
300		
18		
		
$0,2 + 2,5$ $24 + 14$	$0,2 + 2,5$ $24 + 14$	$0,2 + 2,5$ $24 + 14$
8		
110		
PA · UL 94 V0		

V	A	mm ² /AWG
300	18	0.2 + 2.5
300	18	0.2 + 2.5
300	14	24 + 14

min 2 - max 16
VE / on demand GR GR NE AR BL RO G
D/B5



MRT40..FVS
Single block - Blocco unico
Monobloc - Einzelblock

Poles - Póles - Póles - Polzahl


2/16



5,08		
300		
18		
		
0.2 ÷ 2.5 24 ÷ 14	0.2 ÷ 2.5 24 ÷ 14	0.2 ÷ 2.5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
300	18	0.2 + 2.5
300	18	0.2 + 2.5
300	14	24 + 14


min 2 - max 16
VE / on demand GR GR NE AR BL RO G
D/B5



MRT40
Single block - Blocco unico
Monobloc - Einzelblock

Poles - Póles - Póles - Polzahl


2/8



10,16		
600		
18		
		
0,2 + 2,5 24 + 14	0,2 + 2,5 24 + 14	0,2 + 2,5 24 + 14
8		
110		
PA · UL 94 V0		

V	A	mm ² /AWG
600	18	0.2 + 2.5
600	18	0.2 + 2.5
300	14	24 + 14

min 2 - max 8
VE / on demand GR GR NE AR BL RO G
D/B5



MALE PLUG
SCREWLESS
CONNETTORI MASCHIO
A MOLLA
CONNECTEURS MÂLE
RESSORT
STECKERTEIL INVERTIERT
(STIFTKONTAKT)
FEDERKRAFT

Pitch Passo	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Tensione nominale Bemessungsspannung	V
Rated Current Intensità nominale	Corrente nominale Bemessungsstrom	A
Types of cables Type di cavo Type de conducteur	Tipo cavo Leitungs-typen	
Nominal cross section Sezione nominale Section nominale	Sezione nominale Nennquerschnitt	mm ² AWG
Stripping length Lunghezza spelatura Longueur de dénudage	Absolutelänge	mm
Temperature Temperatura Température	Temperatura Temperatur	°C
Housing Corpo isolante Corps isolant	Corpo isolante Isolierrkörper	

IMQ	EN61984
VDE	EN61984
cUL	UL1059 + C22.2 n°158

Poles Pôles Couleurs	Poli Polzahl Farben	X
Other information Autres données	Altre dati Weitere Informationen	Y


How to order Référence de commande	Ordinazione Bestellnummer
MRT40 P10,16 / X A Y N..	
Type Pitch Poles Version Colors Printing	
Tipo Passo Poli Versione Colori Numerazione	
Type Pas Pôles Version Couleurs Marquage	
Type Rastermaß Polzahl Version Farben Bedruckung	

MRT40..A

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl


2/8



10,16		
600		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
600	18	0,2 ÷ 2,5
600	18	0,2 ÷ 2,5
300	14	24 ÷ 14

min 2 - max 8
VE / on demand GR GR1 NE AR BL RO G
D/B5



MRT40..FV

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl


2/8



1016		
600		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA - UL 94 V0		

V	A	mm ² /AWG
600	18	0,2 ÷ 2,5
600	18	0,2 ÷ 2,5
300	14	24 ÷ 14

min 2 - max 8
VE / on demand GR GR1 NE AR BL RO G
D/B5



MRT40..FVS

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Poli - Pôles - Polzahl

2/8



10,16		
600		
18		
		
0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14	0,2 ÷ 2,5 24 ÷ 14
8		
110		
PA · UL 94 V0		

V	A	mm ² /AWG
600	18	0,2 ÷ 2,5
600	18	0,2 ÷ 2,5
300	14	24 ÷ 14

min 2 - max 8
VE / on demand GR GR1 NE AR BL RO G
D/B5

