



Saves Your Energy

PRODUCT CARD

9/13/16

NAC21S.B

2-pólový konektor s odlehčením tahu, vidlice

Kód	NAC21S.B
GTIN	6418677113871
Název	2-pólový konektor s odlehčením tahu, vidlice EnstoNet Černá (1, N)
Popis	Pro pružné, slaněné a plné dráty. Průřezy vodičů: 0,75-4,0 mm ² . Odlehčovač tahu pro kabely s vnějším průměrem 6,2-11,5 mm. Konektory NAC21SL.W a NCC21SL.G s odlehčovačem tahu pro kabely s vnějším průměrem 2,5-8,5 mm. Váha 11,8 g. Póly značeny v závorkách.

Dodavatel Ensto Finland Oy



Technické parametry

Technické údaje

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 11.8 g

Conductor cross-section: 0,75 - 4 mm²

Dimensions l x w x h: 51x29x20

Temperatures

Max. operating temperature: +70 °C

Min. installation temperature: +5 °C

Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Black

Features

Pole markings: 1,N

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 V

Degree of protection: IP20

Rated current: 20 A

ETIM: EC002560

US specific

UL Rated voltage: 250 V

UL Rated current: 16 A

ETIM

ETIM

Width: 29 mm

Length: 51 mm

Height: 20 mm

Balení

Balení

Unit: PCS

Size: 200

Length: 385 mm

Width: 260 mm

Height: 130 mm

Weight (brt): 2.61 kg

Volume: 13.013

Pallet package

Size: 12600

