



Saves Your Energy

PRODUCT CARD

9/14/16

NAC22.B

2-pólový konektor bez odlehčovače tahu, zásuvka

Kód	NAC22.B
GTIN	6418677113857
Název	2-pólový konektor bez odlehčovače tahu, zásuvka EnstoNet Černá (1, N)
Popis	Pro pružné, slaněné a plné dráty. Část pro připojení drátů 0,75-4,0 mm ² . Váha 6,9 g. Póly značeny v závorkách.
Dodavatel	Ensto Finland Oy



Technické parametry

Technické údaje

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 6.9 g
 Conductor cross-section: 0,75 - 4 mm²
 Dimensions l x w x h: 50x29x20

Temperatures

Max. operating temperature: +70 °C
 Min. installation temperature: +5 °C
 Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Black

Features

Pole markings: 1,N

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 V

Degree of protection: IP20

Rated current: 20 A

ETIM: EC002560

US specific

UL Rated voltage: 250 V

UL Rated current: 16 A

ETIM

ETIM

Width: 29 mm

Length: 31 mm

Height: 18 mm

Balení

Balení

Unit: PCS

Size: 500

Length: 385 mm

Width: 260 mm

Height: 130 mm

Weight (brt): 3.7 kg

Volume: 13.013

Pallet package

Size: 31500

