



Saves Your Energy

PRODUCT CARD

9/13/16

## NCC32S.P

### Coupler

Kód	NCC32S.P
GTIN	6418677117404
Název	Coupler EnstoNet Red (1, PE, N)
Popis	For flexible, stranded and solid wires with cross-section 0.75-4.0 mm <sup>2</sup> . Strain-relief for cables with outer diameter of 5.5-12.0 mm and NCC32SL.P for 4.5-11.0 mm.
Dodavatel	Ensto Finland Oy



## Technické parametry

### Technické údaje

UL Wire range: 12 ... 18 AWG

### Dimensions

Weight: 16.8 g  
 Conductor cross-section: 0,75 - 4 mm<sup>2</sup>  
 Dimensions l x w x h: 56x39x20

### Temperatures

Max. operating temperature: +70 °C  
 Min. installation temperature: +5 °C  
 Min. operating temperature: -30 °C ( without mechanical stress )

### Materials

Material: Polyamide 66

### Colors

Color: Red

### Features

Pole markings: 1,PE,N

## Drawing markings

L: 250 mm

## Ratings

Rated voltage: 250 V

Degree of protection: IP20

Rated current: 20 A

ETIM: EC002560

## US specific

UL Rated voltage: 250 V

UL Rated current: 16 A

## Balení

---

### Balení

Unit: PCS

Size: 200

