



**fitted with**

**work equipment**  
**connected load**  
**power consumption**  
**luminous flux**  
**luminous efficacy**  
**light distribution**  
**light colour**  
**color rendering index (CRI)**  
**glare-free**  
**system of protection**  
**class of protection**  
**technology**  
**usage**  
**luminaire body**  
**lamp cover**  
**tubular sections**  
**weight (net)**  
**mains lead**

LED  
 Energy efficiency category A+  
 electronic plug-in transformer  
 100-240 V; 50/60 Hz  
 approx. 6 W  
 approx. 460 lm  
 approx. 77 lm/W  
 direct, wide-angled beam  
 neutral white, approx. 5000 K  
 > 70  
 screen  
 IP 67  
 II with plug-in power supply; III without plug-in power supply  
 switchable  
 pressure switch  
 aluminium, painted, black  
 glass screen  
 flexible metal tube, black  
 approx. 1.7 kg  
 approx. 3 m; mains plug  
 US-ConnectionStandard  
 US-ConnectionStandard  
 US-ConnectionStandard  
 screw-down flange  
 Flood with 30° angle of radiation

**fastening**  
**special features**



BS 1363 A




CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 50 cm  
**Em:** 2969 lx  
**Emax:** 5298 lx  
**Emin:** 1085 lx



**luminous intensity**

