

# Free-standing luminaire LAVIGO - DPS 480/P

121715000-00707559 replaces 121715000-00644130

# Waldmann W

ENGINEER OF LIGHT.



## fitted with

work equipment  
connected load  
power consumption  
power factor  
luminous flux  
luminous efficacy  
light distribution  
direct ratio  
light colour  
color rendering index (CRI)  
glare-free  
luminance  
unified glare rating  
technology  
usage  
luminaire body  
lamp cover  
tubular section  
luminaire base  
weight (net)  
mains lead

fastening  
decorative contrast side parts  
special features

## LED

light colour daylight white, 3000-6500 K

Energy efficiency category A+

LED module

light colour neutral white, 4000 K

Energy efficiency category A+

electronic ballast

220-240V; 50/60Hz

approx. 94 W

approx. 0,966

approx. 11500 lm

approx. 122 lm/W

direct/indirect

approx. 17 %

adjustable white

> 80

conical prismatic screen

< 2800 cd/m<sup>2</sup>

< 16

controlled depending on presence and daylight

multi-function switch

steel/plastic, painted, silver metallic

polycarbonate, clear

steel tube, painted, tubular section upright, silver metallic

C-form flat

approx. 18.5 kg

approx. 3,0 m; mains plug

CEE 7/VII

floor standing base

metallic silver

luminaire head detachable, integrated light- and

presence-detecting sensor PULSE, integrated light

management for biodynamic light PULSE VTL, light forming,

retrofit with EnOcean wireless module PULSE-TALK



CEE 7/VII

## luminous intensity

