REGIOLUX

Category (ETIM): Device mounts Device mounts IP20 Type: SDGOT LED Order number: 18520304100 Configuration: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K LED service life: 50000h L80/B10 Operating device: Electronic driver (1 pcs.) Mains voltage: 230V / 50Hz System performance (W): 56 Luminaire luminous flux 8000 (lm): Luminaire luminous efficacy 139 (Im/W): Energy efficiency class: Ambient temperatures: 10°C / 35°C IP 20, protection class I, Certifications: ENEC10 VDE, F, DIN10500/Food, Indoor, CE

traffic white RAL 9016

Mounting rail system

4020863325535

1531 x 55 x 37

mounting

94051098

Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Housing colour traffic white RAL 9016; Direct, narrow-beam light distribution by means of individual. lens. optic made of acrylic glass. Optically seamless light run. Heat-resistant cables including fixed 3-pole rapid installation plug connector with tool-less phase pre-selection and locating finger.

1.9

Dimensions LxWxH/DxH (mm): 1531 x 55 x 37

Configuration: LED, Colour rendering/Light colour CRI \geq 80 /

4000K

LED service life: 50000h L80/B10 Luminaire luminous flux (lm): 8000 Luminaire luminous efficacy (lm/W): 139 Operating device: Electronic driver (1 pcs.)

System performance (W): 56 Energy efficiency class: A++

Colour of the housing:

Dimensions LxWxH/DxH

Weight (net) (kg):

mounting method:

Commodity code:

EAN-number:

(mm):

Conditions: Suitable for use in ambient temperatures of 10°C

to 35°C

Certifications: IP 20, protection class I, ENEC10 VDE, F,

DIN10500/Food, Indoor, CE

Regiolux GmbH

Type: SDGOT LED 8000 840 ET vw Article number: 18520304100

Product deep link:


http://www.regiolux.de/de/article/18520304100 5 year guarantee after registration on website.

SDGOT LED 8000lm 840 - vw - ET - 18520304100



Lighting technology

Individual.Lens.Optic-direct narrow distribution SDGOT LED 8000 lm 840



η_{LB} 100 % Im/W 139 φ↓/↑ 99 % / 1 % UGRq/I 19.5 / 21.5



Accessories