

DLSB220 LED OPAL COVER - 95 MM



Part number	822721234001
Lampholder:	LED
Light Source:	LED
Wattage (W):	27 W
Finish / RAL:	White RAL9016
Insulation class:	I
Degree of protection:	IP 20
Kelvin:	4000
Power factor:	COS ϕ $\geq$ 0,9
EEL:	A2
Optic:	EXTRA WIDE CIRCLE REFLECTOR ($\Rightarrow$ 75°)
Optic Beam:	2 x 47°
Lightsource lumen output:	3220 lm
Luminaire lumen output:	2510 lm
Lifetime:	50000 h
Percent lumen depreciation:	L80




Description

Recessed round LED downlight for indoors, consisting of:

- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
- Light-tight housing
- Suitable for ceiling tile thickness from 1-25 mm
- Recessed frosted diffuser for optimal light distribution and high homogeneity
- White modular reflector, ABS injection-molded with light-tight connection of LED board
- Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
- Colour rendering index Ra > 80
- Colour tolerance according to MacAdam $\leq$ 3 SDCM
- Also dimmable via TouchDIM®
- Complete with electric converter
- Protection class IP54* (for light emission surface for installation in closed ceilings)

TECHNICAL DATA



TECHNICAL DRAWINGS

