

UWF 10



Colors:

80

- Underwater luminaire, comprising:
- ↳ Technopolymer housing and ring
 - ↳ Flat tempered glass diffuser
 - ↳ Anti-aging silicone gasket
 - ↳ Tear-proof nickered brass cable gland PG11 for cables Ø 6 mm- Ø 10 mm
 - ↳ To ensure protection grade IP68, the luminaire must be powered only by H07RN8-F type cables that are available as an accessory
 - ↳ The LED version is complete with white LED 3000 K
 - ↳ Stainless steel locking screws
 - ↳ Adjustable stainless steel bracket
 - ↳ Must only function totally submerged in fresh water and they must only be powered by a low voltage of 12 V
 - ↳ If the luminaires are even temporarily installed outside the water, the maximum wattage that can be installed is 20 W
 - ↳ UWF 10 LED shall work permanently underwater
 - ↳ To be powered only with 12 V AC safety transformers, available as accessory
 - ↳ IP68 up to 5 meters




UWF 10
LED C/W



UWF 10



UWF 10
C/I



Lamps

	GUS,3	1x4.5 W
	GUS,3	1x50 W
	GY6,35	1x100 W

UWF 10 LED C/W

IK08 6J xx5

LED NUMBER	WATTAGE	ILCOS	LBS	COLOUR/ RAL	CLASS		KELVIN	COS Ø ≥ 0,9	EEL	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	LIFETIME	L	°C	PART NUMBER	REMARKS	EURO
Power LED + 4 m H07RN8 - F 2X1.5 mm²																			
1x4,5 W	1x4,5 W	HRG	-	80	III		3000	•	-	C/W	-	-	-	-	-	-	07042280		

UWF 10

IK08 6J xx5

LAMPHOLDER	WATTAGE	ILCOS	LBS	COLOUR/ RAL	CLASS		KELVIN	COS Ø ≥ 0,9	EEL	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	LIFETIME	L	°C	PART NUMBER	REMARKS	EURO
Halogen																			
GU5,3	1x50 W	HRGS	QR-CB51	80	III		-	•	-	-	-	-	-	-	-	-	01961018		
Halogen + 4 m H07RN8 - F 2x2.5 mm²																			
GU5,3	1x50 W	HRGS	QR-CB51	80	III		-	•	-	-	-	-	-	-	-	-	01958018		

UWF 10 C/I

IK08 6J xx5


LAMPHOLDER	WATTAGE	ILCOS	LBS	COLOUR/ RAL	CLASS		KELVIN	COS Ø ≥ 0,9	EEL	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	LIFETIME	L	°C	PART NUMBER	REMARKS	EURO
Halogen																			
GY6,35	1x100 W	HS GS	QT12-tr	80	III		-	•	-	C/I	-	-	-	-	-	-	01962018		
Halogen + 4 m H07RN8 - F 2x2.5 mm²																			
GY6,35	1x100 W	HS GS	QT12-tr	80	III		-	•	-	C/I	-	-	-	-	-	-	01959018		

CONTROL GEAR

DESCRIPTION	COLOUR	PART NUMBER	EURO
UWF 10			
A0126/T CLASS II IP67 box complete with 1x100VA 220-240/12V transformer for ground and concrete recessed installation (non submersible. Above ground use only).	-	14096120	
A0127/T 1x100VA 220-240/12V safety transformer. Not suitable for installing within A0126 accessory.	-	14423998	
A0128/T 1 x 350VA 240/12V safety transformer.	-	14094920	

OPTIONAL ACCESSORIES


DESCRIPTION	COLOUR	PART NUMBER	EURO
UWF 10			
A0129 CLASS II IP67 wiring box for ground and wall recessed installation (non submersible. Above ground use only).	-	14422018	
A0125 Floor / wall recessing accessory for UWF 10 fitting.	-	14421018	
A0165 Accessory for recessed installations into plastic sheet wall.	-	14002289	
A0235 H07RN-F 2x2.5 mm ² rubber cable supplied and sold in 1 metre units.	-	14018320	




A0126/T




A0127




A0128/T



A0129



A0125



A0165



A0235

