





Light source

Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Mains lead

Design

Fastening

Minimum ambient temperature

Maximum ambient temperature

EAN

Weight without/incl. packaging

Dimensions (dimensional drawing)

Packaging dimensions

Special features

LED

Electronic ballast

100 V; 120 V; 220 - 240 V; AC; 50 Hz; 60 Hz

ca. 31 W

approx. 2.700 lm

approx. 87 lm/W

Cold white

approx. 5.000 K

CRI ≥ 80

Direct; Symmetric

80°/100°

< 4 SDCM

optical film

≤ 27.000 cd/m²

≤ 25

IP 67; I

Switchable

External

Aluminium; Anodised; Aluminium coloured
anodised
Borosilicate; Clear

Built-in plug; Serie 814

mounted version

L-angle; Clamp

-10 °C

40 °C

4013330125127

ca. 2,9 kg; 3,3 kg

A=790 mm

ca. 1.030 mm; 110 mm; 95 mm

Power equipment

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g