

ACRO+




Weatherproof LED luminaire complete with diffuser, comprising:

- Housing made of fiberglass reinforced polyester
- Opal PMMA diffuser for optimal light diffusion and a high light uniformity
- Silicone gasket
- 4000 K multichip LED board
- Stainless steel retaining clips


- Quick ceiling fixing bracket (stainless steel)
- EXTREME versions are suitable for extreme conditions, -30°C
- Emergency and extreme versions have a polycarbonate diffuser, 850°C glow wire
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08



● GR-RAL7035 / Grey RAL7035 / Matt



ACRO+
EQ118
EQ136
EQ158



ACRO+
EQ236
EQ258



Please visit our web site
www.performanceinlighting.com
for the latest updated versions available.


EQ = EQUIVALENT

		Dimensions (LxWxH)	LED Module	lm	W
3103915	ACRO+ EQ136 S/EW 840	Same dimensions 1x36 W	Equivalent lm output 136	2700	24
3103919	ACRO+ EQ236 S/EW 840	Same dimensions 2x36 W	Equivalent lm output 236	5500	51
3103923	ACRO+ EQ236 HO S/EW 840	Same dimensions 2x36 W	Equivalent High lm output 236	8100	59
3103927	ACRO+ EQ158 S/EW 840	Same dimensions 1x58 W	Equivalent lm output 158	4100	33
3103931	ACRO+ EQ258 S/EW 840	Same dimensions 2x58 W	Equivalent lm output 258	6500	59
3103935	ACRO+ EQ258 HO S/EW 840	Same dimensions 2x58 W	Equivalent High lm output 258	10200	73

ACRO+ EQ118

IK03 0.35J xx1


WATTAGE	CLASS	CRI	KELVIN	COS θ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
17.5 W	I	-	80 4000	✓	S/EW	-	-	1900 lm	70	50	70000 h	●	669 mm	3103914



ACRO+ EQ136

IK03 0.35J xx1


WATTAGE	CLASS	CRI	KELVIN	COS θ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
23.5 W	I	-	80 4000	✓	S/EW	-	-	2700 lm	70	50	60000 h	●	1277 mm	3103915
Power LED - dimmable DALI 220-240 V 50/60 Hz														
23.5 W	I	-	80 4000	✓	S/EW	-	-	2700 lm	70	50	60000 h	●	1277 mm	3103916
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz														
23.5 W	I	-	80 4000	✓	S/EW	-	-	2700 lm	70	50	60000 h	●	1277 mm	3103918
Power LED - Emergency 3h - 220-240 V 50/60 Hz														
23.5 W	I	-	80 4000	✓	S/EW	-	-	2700 lm	70	50	60000 h	●	1277 mm	3103917



ACRO+ EQ158

IK03 0.35J xx1


WATTAGE	CLASS	CRI	KELVIN	COS θ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
33 W	I	-	80 4000	✓	S/EW	-	-	4100 lm	70	50	60000 h	●	1577 mm	3103927
Power LED - dimmable DALI 220-240 V 50/60 Hz														
33 W	I	-	80 4000	✓	S/EW	-	-	4100 lm	70	50	60000 h	●	1577 mm	3103928
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz														
33 W	I	-	80 4000	✓	S/EW	-	-	4100 lm	70	50	60000 h	●	1577 mm	3103930
Power LED - Emergency 3h - 220-240 V 50/60 Hz														
33 W	I	-	80 4000	✓	S/EW	-	-	4100 lm	70	50	60000 h	●	1577 mm	3103929



ACRO+ EQ258

IK03 0.35J xx1


WATTAGE	CLASS	CRI	KELVIN	COS θ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
59 W	I	-	80 4000	✓	S/EW	-	-	6500 lm	70	50	60000 h	●	1577 mm	3103931
Power LED - dimmable DALI 220-240 V 50/60 Hz														
59 W	I	-	80 4000	✓	S/EW	-	-	6500 lm	70	50	60000 h	●	1577 mm	3103932
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz														
59 W	I	-	80 4000	✓	S/EW	-	-	6500 lm	70	50	60000 h	●	1577 mm	3103934
Power LED - Emergency 3h - 220-240 V 50/60 Hz														
59 W	I	-	80 4000	✓	S/EW	-	-	6500 lm	70	50	60000 h	●	1577 mm	3103933



ACRO+ EQ236

IK03 0.35J xx1


WATTAGE	CLASS	CRI	KELVIN	COS θ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
51 W	I	-	80 4000	✓	S/EW	-	-	5550 lm	70	50	60000 h	●	1277 mm	3103919
Power LED - dimmable DALI 220-240 V 50/60 Hz														
51 W	I	-	80 4000	✓	S/EW	-	-	5550 lm	70	50	60000 h	●	1277 mm	3103920
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz														
51 W	I	-	80 4000	✓	S/EW	-	-	5550 lm	70	50	60000 h	●	1277 mm	3103922
Power LED - Emergency 3h - 220-240 V 50/60 Hz														
51 W	I	-	80 4000	✓	S/EW	-	-	5550 lm	70	50	60000 h	●	1277 mm	3103921



ACRO+ EQ236 HO

IK03 0.35J xx1


WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
Power LED 220-240 V 50/60 Hz															
59 W	I	-	80	4000	✓	S/EW	-	-	8100 lm	70	50	70000 h	●	1277 mm	3103923
Power LED - dimmable DALI 220-240 V 50/60 Hz															
59 W	I	-	80	4000	✓	S/EW	-	-	8100 lm	70	50	70000 h	●	1277 mm	3103924
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz															
59 W	I	-	80	4000	✓	S/EW	-	-	8100 lm	70	50	70000 h	●	1277 mm	3103926
Power LED - Emergency 3h - 220-240 V 50/60 Hz															
59 W	I	-	80	4000	✓	S/EW	-	-	8100 lm	70	50	70000 h	●	1277 mm	3103925



ACRO+ EQ258 HO

IK03 0.35J xx1


WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
Power LED 220-240 V 50/60 Hz															
73 W	I	-	80	4000	✓	S/EW	-	-	10200 lm	70	50	70000 h	●	1577 mm	3103935
Power LED - dimmable DALI 220-240 V 50/60 Hz															
73 W	I	-	80	4000	✓	S/EW	-	-	10200 lm	70	50	70000 h	●	1577 mm	3103936
Power LED - daylight sensor and PIR detector - 220-240 V 50/60 Hz															
73 W	I	-	80	4000	✓	S/EW	-	-	10200 lm	70	50	70000 h	●	1577 mm	3103938
Power LED - Emergency 3h - 220-240 V 50/60 Hz															
73 W	I	-	80	4000	✓	S/EW	-	-	10200 lm	70	50	70000 h	●	1577 mm	3103937



ACRO+ EQ236 HO EXTREME-30°

IK08 5J xx5

WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
Power LED 220-240 V 50/60 Hz															
59 W	I	-	80	4000	✓	S/EW	-	-	7725 lm	70	50	70000 h	●	1277 mm	3103947



ACRO+ EQ258 HO EXTREME-30°

IK08 5J xx5

WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	LENGTH	PART NUMBER
Power LED 220-240 V 50/60 Hz															
73 W	I	-	80	4000	✓	S/EW	-	-	9600 lm	70	50	70000 h	●	1577 mm	3103948

