

ACRO+ EQ158



Part number	3103928
Lampholder:	LED
Light Source:	LED
Wattage:	33 W
Finish:	GR-RAL7035 / Grey RAL7035 / Matt
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK03 0.35J xx1
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Luminaire lumen output:	4100 lm
L:	L70
B:	B50
Lifetime:	60000 h
Ta MIN luminaire:	-15°
Ta MAX luminaire:	40°




Description

Weatherproof LED luminaire complete with diffuser, comprising:

- Housing made of fiberglass reinforced polyester
- Opal PMMA diffuser for optimal light diffusion and a high light uniformity
- Silicone gasket
- 4000 K multichip LED board
- Stainless steel retaining clips
- Quick ceiling fixing bracket (stainless steel)
- EXTREME versions are suitable for extreme conditions, -40°C
- Emergency and extreme versions have a polycarbonate diffuser, 850°C glow wire
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

