

## ACRO+ EQ158




<b>Part number</b>	3103929
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	33 W
<b>Finish:</b>	GR-RAL7035 / Grey RAL7035 / Matt
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK08 5J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Symmetric extra wide reflector
<b>Luminaire lumen output:</b>	4100 lm
<b>L:</b>	L70
<b>B:</b>	B50
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	5°
<b>Ta MAX luminaire:</b>	40°



### Description

- Weatherproof LED luminaire complete with diffuser, comprising:
- Housing made of fiberglass reinforced polyester
  - Opal PMMA diffuser for optimal light diffusion and a high light uniformity
  - Silicone gasket
  - 4000 K multichip LED board
  - Stainless steel retaining clips
  - Quick ceiling fixing bracket (stainless steel)
  - EXTREME versions are suitable for extreme conditions, -40°C
  - Emergency and extreme versions have a polycarbonate diffuser, 850°C glow wire
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

