

BLIZ SQUARE 40



design by R. FIORATO - F. PAGLIARINI




- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Series of wall and ceiling mounting luminaires for indoor and outdoor use, comprising:

- Body, trim and guard made of die-cast pressed aluminium, painted
- Pressed glass diffuser, painted inside
- Silicone gasket
- Through wiring possible
- Dimmable DALI
- Supplied with SMD self-heat dissipating power LED metal core board: FUTURE-PROOF™
- Stainless steel locking screws
- EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
- Hyper-frequency (HF) sensor operating at a frequency of 5.8 Ghz+/- 75 Mhz
- Powder polyester painting process optimized against UV rays in 13 different steps
- SMART versions are equipped with customised electronic devices that allows energy savings reducing the luminous flux, whilst providing a 30% working flux for safety lighting and reaching 100% flux when necessary
- SMART HF versions are complete with integrated High Frequency sensor that operates from 30% up to 100% of the flux when it detects the presence of people
- SMART DA versions are suitable for use in systems with two separate lines where the demand for 100% of the flux is managed by a push button or line sensor




BLIZ SQUARE 40



BLIZ SQUARE 40
/G

Fixing holes





BLIZ SQUARE 40




OFF
0%




DIM
1% - 100%



BLIZ SQUARE 40
HF




OFF
0%




HF (DETEK)
100%




BLIZ SQUARE 40
EM/3P



OFF
0%



ON
100%



EM/3P - 3h




BLIZ SQUARE 40
SMART HF



OFF
0%




HF (DETEK)
100%




SMART
30%




BLIZ SQUARE 40
SMART DA



OFF
0%




DA
100%



SMART
30%




CEILING SURFACE MOUNTED



A	B
max 2,6 m	Ø 10 m

WALL MOUNTED



A	B
max 1,8 m	Ø 10 m

BLIZ SQUARE 40

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	39 W	I	•	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304650
LED	39 W	I	•	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304647
LED	39 W	I	•	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304651
LED	39 W	I	•	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304648
LED	39 W	I	•	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304652
LED	39 W	I	•	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304649

Power LED - dimmable DALI 220-240 V 50/60 Hz

LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304662
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304659
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304663
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304660
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304664
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304661

BLIZ SQUARE 40 HF

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 230 V 50 Hz															
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304674
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304671
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304675
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304672
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304676
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304673

BLIZ SQUARE 40 SMART HF

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 230 V 50 Hz															
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304686
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304683
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304687
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304684
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304688
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304685


BLIZ SQUARE 40 SMART HF EM/3P

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 230 V 50 Hz															
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304723
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304720
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304724
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304721
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304722
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304725


BLIZ SQUARE 40 SMART DA

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304680
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304677
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304681
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304678
LED	39 W	I		80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304682
LED	39 W	I		80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304679


IK07 2J xx5




IK07 2J xx5




IK07 2J xx5



IK07 2J xx5




IK07 2J xx5



BLIZ SQUARE 40 EM/3P

IK07 2J xx5


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED - Emergency 220-240 V 50/60 Hz														
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304668
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304665
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304669
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304666
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304670
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304667



BLIZ SQUARE 40/G

IK07 2J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz														
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304782
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304779
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304783
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304780
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304784
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304781




Power LED - dimmable DALI 220-240 V 50/60 Hz

LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304788
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304785
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	●	304789
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	●	304786
LED	39 W	I	80	4000	•	S/EW	-	6732 lm	2495 lm	80	10	36000 h	○	304790
LED	39 W	I	80	3000	•	S/EW	-	6732 lm	2515 lm	80	10	36000 h	○	304787

OPTIONAL ACCESSORIES

DESCRIPTION	COLOR	PART NUMBER
BLIZ SQUARE 40		
Polycarbonate diffusor		310255



310255