

## Product Info




<b>Item code</b>	D06K/84DD-SP
<b>Installation type</b>	suspension
<b>Environments</b>	hallway, conference hall, office, retail areas, industrial areas, study areas, places of worship
<b>Mounting type</b>	surface
<b>Body</b>	Die-cast light alloy cap. High resistance composite technopolymers hooks.
<b>Painting</b>	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
<b>Screws</b>	AISI 304 stainless steel screws.
<b>Seals</b>	Silicone Rubber.
<b>Standard Colour</b>	SP   Brushed aluminium
<b>Option colors</b>	BE   embossed black




## Dimensions

<b>Total device height (mm)</b>	410
<b>D: Total diameter device (mm)</b>	420



## Optical System

<b>Optical System</b>	Safety tempered protective glass, with light diffusing texture.
<b>Beam</b>	diffuse
<b>Emission</b>	direct
<b>Reflectors</b>	Extra-pure aluminium reflector.
<b>Adjustable</b>	No



## Sources


<b>MacAdam</b>	Step 2
<b>Output Flux</b>	4750 lm
<b>Source power</b>	43W
<b>Source type</b>	LED COB
<b>Temperature Colour</b>	4000K CRI>80

---

## Electrical

<b>Ballast type</b>	DALI.
<b>Frequency</b>	50-60Hz
<b>Lifetime</b>	60.000h L90B10 (Ta=25°C)
<b>Mounting ballast type</b>	Integral
<b>Voltage</b>	220-240V
<b>Separate ignition</b>	No
<b>Emergency 1E</b>	No
<b>Emergency 3E</b>	No

## Photometrics



h (m)	∅ (m)	$\gamma=0.0$ $\alpha=\beta=97^\circ$	Emed (lx)
1.00	2.29		777
2.00	4.57		194
3.00	6.86		86
4.00	9.14		49
5.00	11.43		31

## Optional Accessories

### Mounting



#### **ACS/KIT1-DD-N**

For DALI models. Suspension kit DALI extendable from 0.7 to 1.5m. Injection moulded ceiling rose with an independent anchoring base. Mechanical suspension with flexible rope in galvanized steel. Terminal block two poles plus earth with security cable clamp. Electric wire with extendable spiral 3x1mm<sup>2</sup> cross-section H05VVH8-F and wire 2x0.5mm<sup>2</sup> cross-section for DALI signal. Suitable for indoor application. -N BLACK



#### **ACS/KIT2-DD-N**

For DALI models. Suspension kit DALI extendable from 1.5 to 3m. Injection moulded ceiling rose with an independent anchoring base. Mechanical suspension with flexible rope in galvanized steel. Terminal block two poles plus earth with security cable clamp. Electric wire with extendable spiral 3x1mm<sup>2</sup> cross-section H05VVH8-F and wire 2x0.5mm<sup>2</sup> cross-section for DALI signal. Suitable for indoor application. -N BLACK