

TELLUX LARGE D44 / D44 TELLUX T315 LED COB HIGH FLUX / TELLUX LARGE T315 LED COB HIGH FLUX WS / D44K/T3-2LWN-WS

Product Info




Item code	TELLUX LARGE D44 / D44K/T3-2LWN-WS
Category	Walk-over
Environments	urban landscape, façades and architectural works, wellness, hallway, conference hall, places of worship, residential lighting
Mounting type	with rough-in housing
Body	Corrosion resistant die-cast aluminium body. High impact resistant composite technopolymer housing box. AISI 316 stainless steel frame sandblasted.
Painting	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Static load	5000Kg
Standard Colour	IS stainless steel frame sandblasted



Dimensions

Weight (kg)	8.8
D: Total diameter device (mm)	315
Volume piece packed (m³)	0.046




Optical System

Diffuser	Tempered safety glass - 10 mm thickness, mechanical and thermal shock resistant.
Optical System	PC with aluminium coating reflector.
Beam	wall washer
Emission	direct
Adjustable	No
Tilt	Fixed optic



Photometrics



Sources

MacAdam	Step 3
Output Flux	4341 lm
Source type	LED COB
System power	43W
Temperature Colour	4000K CRI>80

Electrical

Ballast type	ON-OFF.
Frequency	50-60Hz
Lifetime	50.000h L80B10 (Ta=25°C)
Line input	Pre-wired and tested with resin sealed watertight H07RN-F cable (for a fast and secure connection to the main power line, use ACS/CR1 connector or similar).
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No

Optional Accessories

Electrical

**ACS/CR1**

Fast IP68 connector 1bar (10m-1h) for cable Ø7-12mm - 3x1.5mm.

**ACS/CR6**

4 ways IP68 wiring box for cable Ø5-14mm - 3x1,5mm.