

THOR D51 / D51 THOR/01 / THOR/01 LED - LT-MAL / D51/01-LWWLT-MAL

Product Info



Item code	THOR D51 / D51/01-LWWLT-MAL
Category	Step light, Wall recessed
Environments	urban landscape, façades and architectural works, wellness, hallway, places of worship
Mounting type	with rough-in housing
Body	Housing and trim in die-cast aluminum, resistant to corrosion.
Painting	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Standard Colour	MAL aluminium grey (metal)
Option colors	MGR graphite satin finish (metal)




Dimensions

Total device width (mm)	100
Total device length (mm)	100
Weight (kg)	0.6
Volume piece packed (m³)	0.002



Optical System

Optical System	Safety tempered glass.
Beam	lighting blade
Emission	direct
Reflectors	Extra-pure aluminium reflector.
Adjustable	No



Sources

MacAdam	Step 3
Output Flux	9 lm
Source type	LED
Source power	3W
Temperature Colour	3000K CRI>80

Electrical

Ballast type	DALI
Frequency	50-60Hz
Lifetime	50.000h L80B50 (Ta=25°C)
Line input	Line entry: prewired with (EN 60598-1) cable type H07RN-F with diameter between 7,5 and 12mm.
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No

Optional Accessories


Rough-in housing



D51/01-CI

For models D51 thor/01. Rough-in housing high stress resistance composite technopolymer.


Pole



D51/01-CM-AL

For models D51 thor/01. Folded stainless steel floor installation braked. Fixing on concrete base or suitable paving. -AL ALUMINIUM

Mounting



D51/01-MS-AL

For models D51 thor/01. Wall bracked installation. -AL ALUMINIUM